SCRUTINEERING CHECKLIST											
BOAT TYPE/CLASS:(c	F8 - ADV - STD -						SUPER STD - SPORTS				
BOAT No:		DATE:					Bore	Size	: 5	55mm /	/ 60mm
EVENT:		REGO I	No:				•				
DRIVER NAME:											
Co-DRIVER NAME:											
This	is a summary only, ple	ase con	sult PE	ORC Co	mpet	etion rules	and Spe	cifica	tion	S.	
ITEM	REQUIREMENT	REMARKS						STATUS			OMMENTS
CRAFT	Safe Design Correct Length	No sharp edges or protrusions 2450mm minimum					F	/	F	•	
DOT Registration Number	Correct Position Correct Dimensions Background Size	Near transom, less than 75mm from gunnel 150mm high x 25mm wide 10mm white surround						) /	F		
DOT HIN (If applicable) & Rego sticker	Current Correct Position	Legible, matches Registration number port side next to the registration number						<b>)</b> /	F	•	
Race ID Number	Correct Position	As per PDRC Specifications 10,110,210,310,410,510,610						) /	F	•	
Buoyancy	Sufficient Correct Type Secured and Sealed	Refer to rules PDRC Specification 700-715					<sup>5</sup> F	) /	F	•	
Tow Point	Correct Position	As per PDRC specification 35,160,260,350,440,555,660.					F	) /	F	•	
Motor Restraint	Webbed Type Restraint	Made by "Commercial Sewing".See Specification Rule 980 Motor not to tilt above horizontal 10mm eye bolts,8mm shackles						) /	F		
Hydraulic Jack Restraints	Prevents the Slide Block Exiting the Slide	As Per Specification 981.Must have 2 x 10mm Bolts and a bar min thickness 3mm					F	<b>)</b> /	F	•	
Lanyard	Aftermakket may be used. Operational	Lanyard incorporated in switch.1M max stretched. Stops motor when detatched					F	) /	F	•	
Fuel Tanks	Approved Fuel Tank	Secured with non elastic material						) /	F	•	
Fuel Lines and Filters	OEM fitting to the Motor	Inline fuel filters exect OEM to only be fitted before the motor						/	F	•	
Wet Suit	Full Length arms and legs	One for each competitor zips functional					F	/	F	•	
P.F.D	Type 1, level 100,150 or Type 2 Level 50	As per PDRC Specification 805-808					F	/	F	•	
Helmets	(AS)1698:1988 (AS/NZS)1698:2006 (UNEC)22.05	One for each competitor As per PDRC Specification 810					F	/	F	•	
Safety Rope	In a Throw Bag	As per Specification 820(12metres)					F	<b>)</b> /	F		
Paddles	2 Paddles in all Dinghy's and 1 in Solo	Accessible. No soft plastic, no sharp edges 600mm handle, 300mm² blade					s F	/	F		
FOOTWEAR	Strong and Safe	No sanda	als or th	nongs ([	Dive bo	oots)	F	/	F		
Recreational Skippers Ticket	Driver or Co Driver	MUST be	e carrie	d in the	craft r	oom at ALL	F	/	F		
Passed by:											